# FLU TED



"As an architect, you design for the present, with an awareness of the past for a future which is essentially unknown"

Norman Foster









### ABOUT US

At Sanish Laminate, we are passionate about transforming spaces with our exceptional design range. We bring you a bout a transformation design range. We bring you a wide range of high quality products that blend style, durability, and affordability. Our commitment to innovation and custome satisfaction sets us apart, as we strive to create a similar to the strip of t





















6275 RW / DARKWOOD SLATS







88

GYEN SM / STARPHNOS BONE NO


















6274 UG / ASH LINE WOOL




























10












-















G / FLUTED WOOD DARK

#### INDEX

Design No.	Finish	Page No.	Design No	0. Finish	Page No.
6012	UG	6	6283	UG	41
6012	UG	22	6284	UG	40
6012	UG	28	6285	UG	33
6030	UG	6	6286	UG	32
6031	UG	18	6287	UG	34
6086	SM	14	6288	UG	35
6086	UG	22	6289	UG	31
6086	UG	28	6290	UG	30
6271	SM	7	6291	UG	11
6272	UG	23	6292	UG	10
6273	UG	21	6293	UG	16
6274	UG	20	6294	UG	17
6275	BW	12	6295	UG	8
6276	BW	13	6295	BW	9
6277	UG	27	6296	UG	24
6279	UG	37	6296	BW	25
6280	SM	19	6320	SM	39
6281	SM	15	6378	UG	26
6282	UG	29	6905	UG	38

#### TECHNICAL SPECIFICATION

MOMENTES	SPECIFIED VALUES AS PER IS:2046-1995	SANISH CONFORMS
Resistance to surface Wear	350 (revolution)	4
Resistance to immersion in boiling water - Moss increase (%) - Thickness increase	10.0 Max 11.8 Max	\( \tau \)
Resistance to dry heat 180 degrees C	Not worse than 4	~
Dimensional stability at deviated temperature - Longitudinal (%) - Transverse (%)	0.5 Max. 0.9 Max.	*
Dimensional stability  At 20 degrees C  - Longitudinal (%)  - Transverse (%)	0.375 Max. 0.60 Max.	<b>*</b>
Resistance to impact by small diameter ball	20N Min.	~
Resistance to cracking	Not worse than 4	V
Resistance to scratching	2N Min.	·
Resistance to staining	Not worse than 5	·
Resistance to colour change (weel standards) - In Xenon arc light - In enclosed Carbon arc light	Not worse than 6 Not worse than 5	*
Resistance to cigarette burns	Not worse than 3	~
Resistance to steam	Not worse than 4	V
Appearance	Should be free from foreign particles	<b>*</b>

BIT health many need has valid four productional &



506 2440nm (220nm (844)

Product conformity to: Entire European Standard - Ed EN 43b, American Nama (5-5, Ed. Churasu of Indian Standard) is 20

Some services over a process of the process of the

use or subsequent sale of any product, to any person or entity.

Care & Mantenance: Cleaning should be carried out with a soft most cottle and warm soop solution. Do not use detergenor contains



\_\_\_